

LED DOWNLIGHT COB SERIES

INDOOR LIGHTING

Technical Data

Features

- High Performance COB Chips
- Housing: Die Cast Aluminum
- Thermal Conductivity: 226 W/m·K
- Led: Bridgelux
- CRI: Ra>80
- Power Factor: >0.90
- Driver: Azood
- Driver Efficiency: >90%
- Surge Protection: 2.5KV
- Electrical: 170-265V, 50/60Hz
- Operating Temperature: -20~40°C
- TM21: L80B10<50,000H
- Lifetime: 50,000H
- Warranty: 5 years



Optical options:



Model	Power	Voltage	Lumen	Color Temp	CRI	PF	IP	Ring Dimension	CUT-OUT mm
AL07C-0075-V600	7W	170-265V	595LM	6500K	>80	0.9	IP20	Ø90	Ø70
AL07C-0075-V400	7W	170-265V	595LM	4000K	>80	0.9	IP20	Ø90	Ø70
AL07C-0075-V300	7W	170-265V	595LM	3000K	>80	0.9	IP20	Ø90	Ø70
AL20C-0145-V600	20W	170-265V	2000 LM	6500K	>80	0.9	IP20	Ø165	Ø145
AL20C-0145-V400	20W	170-265V	2000 LM	4000K	>80	0.9	IP20	Ø165	Ø145
AL20C-0145-V300	20W	170-265V	2000 LM	3000K	>80	0.9	IP20	Ø165	Ø145
AL30C-0200-V600	30W	170-265V	3000 LM	6500K	>80	0.9	IP20	Ø230	Ø200
AL30C-0200-V400	30W	170-265V	3000 LM	4000K	>80	0.9	IP20	Ø230	Ø200
AL30C-0200-V300	30W	170-265V	3000 LM	3000K	>80	0.9	IP20	Ø230	Ø200
AL40C-0200-V600	40W	170-265V	4000 LM	6500K	>80	0.9	IP20	Ø230	Ø200
AL40C-0200-V400	40W	170-265V	4000 LM	4000K	>80	0.9	IP20	Ø230	Ø200
AL40C-0200-V300	40W	170-265V	4000 LM	3000K	>80	0.9	IP20	Ø230	Ø200
AL30C-S200-V600	30W	170-265V	3000 LM	6500K	>80	0.9	IP20	Ø250	-
AL30C-S200-V400	30W	170-265V	3000 LM	4000K	>80	0.9	IP20	Ø250	-