

LED DOWNLIGHT DOB Series

Technical Data



Features

Housing: Thermoplastic
Led Chip: Sanan (SMD)
CRI: Ra>80
Power Factor: >0.5
Driver: on board (DOB)
Driver Efficiency: > 90%
Protection: IP20
Surge Protection:500V
Electrical:AC 185-265V ,50/60Hz
Storage Temperature:-20 : +60 °C
Working Temperature:-20 : +45 °C
Lifetime: 30,000H

Functions

On/off



Optical options:



3 YEARS WARRANTY

A2000 DOB DRIVER

SANAN LED SMD

Model	Power	Voltage	Frequency	Current	Lumen	CRI	CCT	Lifetime	PF	Cut Out
AL04D-V00	3.5W	185-265V~	50/60Hz	0.04A	240Lm	80	6500K	30000H	0.5	76 mm
AL04D-V03	3.5W	185-265V~	50/60Hz	0.04A	240Lm	80	3000K	30000H	0.5	76 mm
AL15D-V00	15W	185-265V~	50/60Hz	0.14A	1200Lm	80	6500K	30000H	0.7	150 mm
AL15D-V04	15W	185-265V~	50/60Hz	0.14A	1200Lm	80	4000K	30000H	0.7	150 mm
AL20D-V00	20W	185-265V~	50/60Hz	0.26A	1700Lm	80	6500K	30000H	0.7	200 mm
AL20D-V04	20W	185-265V~	50/60Hz	0.26A	1700Lm	80	4000K	30000H	0.7	200 mm