

LED Street Light EG Series


STREET & URBAN LIGHTING

Technical Data ECO Group Series



Features


- Housing: Die-cast Aluminum
- Thermal Conductivity: 96 W/m·K
- LED: SANAN
- CRI: Ra>70
- SDCM: <6
- Power Factor: >0.9
- THD: <15%
- Driver: Philips
- Driver Efficiency: >88%
- Protection: OTP, OCP, OVP, SCP
- Surge Protection: 6 - 20kv
- Ingress Protection: IP66
- Impact Test: IK08
- Electrical: AC100-305V, 50/60Hz
- Operating Temperature: -40~50°C
- TM21: L90B10>50,000H
- Lifetime: 50,000H



Functions

ON/OFF or Photocell

Optical options:



150lm/w

5 YEARS WARRANTY

Model	Power	Voltage	Frequency	Lumen	Color Temp	PF	IP	Dimension
AL050EGS-0485-V6PP	50W	AC100-277V	50/60Hz	7500lm	6500K	0.95	IP66	485*210*70mm
AL050EGS-0485-V4PP	50W	AC100-277V	50/60Hz	7500lm	4000K	0.95	IP66	485*210*70mm
AL050EGS-0485-V3PP	50W	AC100-277V	50/60Hz	7500lm	3000K	0.95	IP66	485*210*70mm
AL100EGS-0538-V6PP	100W	AC100-277V	50/60Hz	15000lm	6500K	0.95	IP66	538*238*102mm
AL100EGS-0538-V4PP	100W	AC100-277V	50/60Hz	15000lm	4000K	0.95	IP66	538*238*102mm
AL100EGS-0538-V3PP	100W	AC100-277V	50/60Hz	15000lm	3000K	0.95	IP66	538*238*102mm
AL150EGS-0602-V6PP	150W	AC100-277V	50/60Hz	22500lm	6500K	0.95	IP66	602*276*105mm
AL150EGS-0602-V4PP	150W	AC100-277V	50/60Hz	22500lm	4000K	0.95	IP66	602*276*105mm
AL150EGS-0602-V3PP	150W	AC100-277V	50/60Hz	22500lm	3000K	0.95	IP66	602*276*105mm
AL200EGS-0607-V6PP	200W	AC100-277V	50/60Hz	30000lm	6500K	0.95	IP66	607*311*112mm
AL200EGS-0607-V4PP	200W	AC100-277V	50/60Hz	30000lm	4000K	0.95	IP66	607*311*112mm
AL200EGS-0607-V3PP	200W	AC100-277V	50/60Hz	30000lm	3000K	0.95	IP66	607*311*112mm
AL250EGS-0607-V6PP	240W	AC100-277V	50/60Hz	36000lm	6500K	0.95	IP66	607*311*112mm
AL250EGS-0607-V4PP	240W	AC100-277V	50/60Hz	36000lm	4000K	0.95	IP66	607*311*112mm
AL250EGS-0607-V3PP	240W	AC100-277V	50/60Hz	36000lm	3000K	0.95	IP66	607*311*112mm